

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number  
**WO 2004/057151 A1**

(51) International Patent Classification<sup>7</sup>: **E21B 33/138**,  
17/10, 21/00

(21) International Application Number:  
PCT/GB2003/005520

(22) International Filing Date:  
17 December 2003 (17.12.2003)

(25) Filing Language: English

(26) Publication Language: English


(30) Priority Data:  
0229865.1 21 December 2002 (21.12.2002) GB

Parkstraat 83-89, NL-2514 JG The Hague (NL). PETRO-  
LEUM RESEARCH AND DEVELOPMENT N.V.  
[NL/NL]; De Ruyterkade 62, Willemstad, Curacao (AN).  
SCHLUMBERGER CANADA LIMITED [CA/CA];  
525 - 3rd Avenue S.W., Calgary, Alberta T2P 0G4 (CA).  
SCHLUMBERGER SEACO INC. [PA/PA]; 8 Calle  
Aquilino de la Guardia, Panama City (PA). SCHLUM-  
BERGER HOLDINGS LIMITED [—/—]; P.O. Box  
71, Craigmuir Chambers, Road Town, Tortola (VG).  
SCHLUMBERGER OILFIELD ASSISTANCE LIM-  
ITED [—/—]; Craigmuir Chambers, Road Town, Tortola  
(VG). SCHLUMBERGER OVERSEAS S.A. [PA/PA];  
8 Calle Aquilino de la Guardia, Panama City (PA).  
SCHLUMBERGER SURENCO S.A. [PA/PA]; 8 Calle  
Aquilino de la Guardia, Panama City (PA). SERVICES  
PETROLIERS SCHLUMBERGER [FR/FR]; 42, rue  
Saint-Dominique, F-75007 Paris (FR).

(71) Applicants (for all designated States except US): SCHLUMBERGER TECHNOLOGY B.V. [NL/NL]; (72) Inventors; and  
(75) Inventors/Applicants (for US only): COOPER, Iain

[Continued on next page]

(54) Title: WELLBORE CONSOLIDATING TOOL FOR ROTARY DRILLING APPLICATIONS



(57) Abstract: A subpart (430) of a drill string (211) is described having an outer circumferential surface which is contoured and adapted to engage the wall of the borehole with a small angle of attack while exerting during rotary drilling operations an compacting pressure on mud cake and/or cuttings present in the annulus between the drill string and the borehole.

WO 2004/057151 A1